



Glass Lined Bottom Outlet Valves

60° Bottom Outlet Valves

Our bottom outlet valves are available with hand wheel, actuator and lateral actuator. Outer finish colour can be chosen from the customer. Also a glass lining in white enamel (email350) is possible. The valve is easy to clean, low-maintenance and is in accordance to the QHD guideline

The modular construction includes:

- 60° valve body steel welded
- Pneumatic actuator made of stainless steel
- Bellow made of TFM with 8 conclusions
- Valve seat made of TFM1600 with integrated gaskets
- Outer finish painting blue
- Flush nozzle DN15, can be used for sample probes
- Emergency opening
- Temperature probe 2xPT100 possible

Designed in accordance to DGRL 97/23/EG PED, Category II, Module A1 with CE marking and declaration of conformity.

Body with flange and loose flange. Connection to ANSI nozzles or other standards through changing of loose flange possible.

Production to "TA-Luft" with bellow and safety packing as well as a connection bore for bellow monitoring.



Our 45° valve is still available, especially for replacement purchase. They are modified with elements from the new 60° valve (bellow, actuator, valve seat etc.). Both constructions are in accordance to TA-Luft.

Our attention was the reduction of the component parts and a low-maintenance. Temperature probe, actuator and limit switch (NAMUR) can be refitted.

We can deliver our valve VB (=45° with glass lined spindle and packing) in request.



Beside of the standard design we can offer our glass lined valves with a special design.

GLASS LINING TECHNOLOGIES

JOBGING FOUNDRY

FITTINGS AND VALVES

DRAINAGE TECHNOLOGY

ENGINEERING

Düker GmbH & Co. KGaA
Hauptstraße 39-41
D-63846 Laufach
Germany

Phone +49 6093 87-0
Fax +49 6093 87-246

Internet: www.dueker.de
E-Mail: info@dueker.de